

TECHNICAL DATA SHEET

LIGHTON

A Height Access Helmet

Product Introduction:

- This lightweight design mountaineering safety helmet combines advanced safety and superior comfort, making it ideal for various demanding environments.
- The ABS shell ensures outstanding impact resistance & durability, while also offering superior heat resistance to safeguard the wearer in high-temperature conditions.
- Designed to meet ANSI Z89.1, Type 1, Class-E standard, it ensures maximum protection for the wearer in various high-risk environment.

Features:

- ABS provides excellent impact resistance, making these peak less helmets, effective in protecting against shocks & collisions.
- Non-contact sweat band maximizes comfort, long time use.
- 6-point textile suspension with ratchet fit adjustment allows for quick and easy adjustments to ensure a secure and comfortable fit.
- This does not add significant weight, which is essential for long climbs and reducing overall fatigue.
- Compatible with head & face PPE accessories.
- 'Y' type chinstrap, Holds the shell perfectly for universal fit.
- Excellent rain management system to effectively reduce the flow of water down the neck

Benefits:

- **Cost-Effective:** Choose proper helmets proper application. The ABS material has excellent impact resistance, making it suitable for use in harsh environments.
- **Regulatory Compliance:** Assists in meeting safety and environmental regulations by providing protection against falling objects
- **Climbing Protection:** Meets the standard for mountaineering equipment, ensuring protection against impact from falling objects, penetration, and stability during falls.
- **Field of Vision:** Designed to provide a wide field of vision, crucial for safety in dynamic environments.
- **Safety Improvement:** The textile suspension system with a ratchet fit mechanism allows for easy and precise adjustment, ensuring a secure and comfortable fit.
- **Durability:** ABS is resistant to many chemicals, including acids, alkalis, and oils, making it suitable for use in industrial environments where exposure to hazardous substances is possible.



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com

Product Specifications:

Model: LIGHTON
Construction: ABS (Acrylonitrile Butadiene Styrene)
Ventilation: Non ventilated
Variants: Textile ratchet fit
Weight: : 460 grams
Color: : White, Navy blue
Accessories slot size: 30 mm.
Internal vertical clearance: 46 mm.
Wearing height: 80 mm.
Circumference of Headband: 520-630 mm.
Cradle width: 21 mm.
Chin strap width: 15 mm
Packaging: 20 pcs. per carton
Standard: ANSI Z89.1, Type 1, Class-E

Textile Ratchet Fit



INNER VIEW



SIDE VIEW



TOP VIEW

Applications :

- The ABS shell provides excellent protection against falling objects which ensures the wearer's safety in case of an accident. Best Used in industries where there is a hazard of falling from the height.
- ABS is resistant to many chemicals, including acids, alkalis, and oils, making it suitable for use in industrial environments where exposure to hazardous substances is possible.
- The helmet can withstand different weather conditions without degrading, ensuring consistent performance in diverse outdoor environments Ideal for high-altitude tasks.

Industry :

These helmets are utilized for their protective and practical features in various industries such as



Construction



Heavy Manufacturing



General Manufacturing



Marine




Steel



Automobile



Food & Breweries



Oil & Gas



Power



Pharmaceutical



Chemical



Agriculture



Transportation



FMCG



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com

Safety Information :

- When worn and maintained properly, safety helmets do a great job of protecting your head from a single impact.
- Excessive discoloration of the shell color of the surface may indicate a loss of strength. Such helmets should be discarded
- All components, shells, harnesses, headbands, and accessories should be visually inspected at least weekly.
- Helmets with sound shells but with damaged, excessively dirty, or defective harness components should be withdrawn from service and the complete harness and cradle replaced.

Usage Instructions :

- Place the helmet squarely on your head, ensuring it covers the top of your forehead and sits level.
- Turn the ratchet knob present at the back side until the helmet fits snugly and comfortably.
- Adjust the chin strap length to ensure a tight fit without causing discomfort.
- Turn the ratchet knob to the left and loosen the chin strap to put the helmet off.

Storage :

- Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)
- Shell may be stored in the dark for up to 3 years
- Do not store in direct / high heat or sunlight as this may distort the suspension

