



UI 1211 - Safety Helmet

STANDARD : IS 2925:1984, DGMS Approved

INDUSTRY

Iron & steel
Cement
Automotive
Power & utilities
Metals & mining

IDEAL APPLICATIONS

Construction & projects works
Material handling
Shop floor
Packaging
Maintenance

SPECIAL FEATURES



COLOURS:



COMPONENT	MATERIAL	ADVANTAGES
Shell	HDPE (High density poly ethylene)	Resistant to high level impact
Peak	HDPE	48 mm, peak protects eye & face from falling objects
Brim	HDPE	Rim around the shell, drains rain water
Cradle	Plastic	6-point adjustment, perfect load distribution
Head band	Plastic	Universal fit, dia. 53 cm - 61 cm
Sweat band	Brushed cloth on foam	Sweat absorbent, long time use
Chin strap	PP	Holds the shell, universal fit
Chin strap clip	Nylon	Attachment between shell and chin strap
Nape strap	Plastic	Fully adjustable, smooth & universal slip fit

FEATURES

Shell made of HDPE compound

Dome shape to provide complete coverage

Smooth finish - solid colour resin for a permanent, no-chip, no-peel finish

Greater impact resistance and crack resistance

6-point plastic suspension with slip fit adjustment

Adjustable chin strap for customized fit and comfort

High quality sweat band provides comfort

Radiant heat resistivity higher than ABS helmets yet light weight

Designed for use in industries where there is a hazard, which can damage skull

APPLICATION

Protects head from falling objects

Protects splashes, spatters etc.

STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)

Shell may be stored in the dark for up to 5 years

Do not store in direct / high heat or sunlight as this may distort the shell

CLEANING

Clean using warm soapy water and soft cloth

Do not use solvents or abrasives

WEIGHT

Slip fit - 320 grams

PACKING

50 pieces per carton



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com