



## 6PAU - Face Shield

STANDARD : EN 166, ANSI Z87.1

### INDUSTRY

Pharmaceutical  
Chemical  
Cement  
Construction  
Automotive

### IDEAL APPLICATIONS

ARC welding  
Heavy, medium, light gas welding  
Atomic hydrogen welding  
Heavy, medium, light cutting  
Torch brazing  
Spot welding, soldering

### SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



CHEMICAL SPLASH PROTECTION



MEDIUM IMPACT RESISTANT

COMPONENT	MATERIAL	CLIP ATTACHMENT	ADVANTAGE
Visor	PVC	Non-universal (UDYOGI ultra helmet)	Covers the entire facial region

LENS	FILTER	COLOUR	LENS SIZE	WEIGHT
Glass	DIN (customized), Clear (customized)	Dark Green, Clear	(4 1/2" X 3 1/2" inch (114 mm X 89 mm)	290 g

### FEATURES

- Flip type front window with clear and DIN glass, extend fully to cover a wearer's face
- Designed to worn with Udyogi 'Ultra' helmet
- Provides full protection against splashes, spatters etc.
- Lens filter DIN glasses, protects IR rays emitted from welding related techniques
- Protects against 99.9% UV protection
- Protections against high-speed impact
- Fits over the spec
- Best optical quality ( Astigmatic refractive power, prismatic refractive power, and light diffusion )
- Suitable for different work environment

### APPLICATION

- Can be used where eye & face exposed to welding, cutting etc.
- Protects face exposed to splashes, high speed flying small & medium fragments

### STORAGE

- Can be stored in the dark for up to 1 year
- Do not store direct / high heat or sunlight as this may distort
- Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

### CLEANING

- Clean cloth can be used

### PACKING

- Cartoon



**THADHANI®**  
The Experts in Safety... Since 1947

**J.THADHANI & CO.**

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com