



FC 58 - Face Shield

STANDARD : Meets ANSI Z87.1, EN 166

COMPONENT	MATERIAL	ADVANTAGE
Visor	Poly chloride	Covers the entire facial region

COMPONENT	COLOUR	SIZE	THICKNESS	IMPACT RESISTANCE
Visor	Clear	(8 X 15 1/2) inch (203 mm X 394 mm)	1 mm	B (120 m/s)

FEATURES
Poly chloride, transparent mask that extend fully to cover a wearer's face
Edges fitted with aluminium beading for easy adjustment to face contour
Protective films on both sides (Prevent damages and scratches during transportation)
Protects against 99.9% UV protection
Provides wide vision
Protection against high-speed impact
Protects against splashes
Fits over the spec
Best optical quality (Highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion)
Suitable for different work environment

APPLICATION

Protects face exposed to splashes, high speed flying small & medium fragments

Also protects face against irritating mist and potentially infectious materials

STORAGE

Can be stored in the dark for up to 1 year

Do not store direct / high heat or sunlight as this may distort

Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING

Clean cloth can be used

PACKING

125 pcs per cartoon

SERVICES

Pharmaceutical

Chemical

Cement

Construction

Automotive

IDEAL APPLICATIONS

Chemical handling

Labs

Chipping

Paint shop

Material handling

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



CHEMICAL SPLASH PROTECTION



MEDIUM IMPACT RESISTANT



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com