



FC 1000 - Face Shield Carrier

STANDARD : EN 166, ANSI Z87.1

INDUSTRY	IDEAL APPLICATIONS
Pharmaceutical	Chemical handling
Chemical	Labs
Cement	Grinding
Construction	Paint shop
Automotive	Material handling

SPECIAL FEATURES



LIGHT WEIGHT



FLIP UP PROTECTION



ANTI FOG COATING



HARD COATING



CHEMICAL SPLASH PROTECTION



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Visor	Polycarbonate	Covers the entire facial region

COMPONENT	COLOUR	OPTICAL CLASS	FILTER	SIZE	THICKNESS	IMPACT RESISTANCE	LIQUID SPLASH PROTECTION	MOLTEN METAL PROTECTION	COATING
Visor	Clear	I	2C - 1.2	(10 ^{1/2} X 15 ^{1/2}) inch (275 mm X 400 mm)	2 mm	A (T) B (190 m/s)	3	9	K, N

FEATURES

Flip up with fully adjustable ratchet type, transparent polycarbonate face shield

Soft sweat band attached with the LDPE head band

Provides wide vision

Anti-fog & hard coating on lens with chin guard

Protects against 99.9% UV protection

Protects against liquid splash, molten metal splash

Protections against high-speed impact

Fits over the spec

Best optical quality (Highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion)

Suitable for different work environment

APPLICATION

Protects face exposed to splashes, high speed flying small & medium fragments

Also protects face against irritating mist and potentially infectious materials

STORAGE

Can be stored in the dark for up to 1 year

Do not store direct / high heat or sunlight as this may distort

Can be stored and transported in their original cartoons at ambient temperature (0° C to 30°C)

CLEANING	WEIGHT	PACKING
Clean cloth can be used	378 g	Cartoon



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com