



# V-2428

## Convex - Cup Seam Style

Products available with below approvals



Class FFP1, FFP2 and FFP3 classes available



### FEATURES AND BENEFITS



#### Anti-Clogging

- Allow to use in multiple shift



#### Compatible with other PPE

- Non-interference with other PPE - eye, hearing & head protection



#### Convex Cup Seam Style

- Popular face fitting, high performance
- No interference with communication
- Maintains high integrity of filter media
- Accommodates facial movements
- Classic collapse-resistance shell with seamed filter cover



#### Tough Shell

- Well-integrated structure maintains the shape disallowing collapse



#### Absorbent Carbon Granules Sandwiched Fabric Layer (V2425, 2426, 2424, 2425, 2428, CN95OV)

- For absorption of nuisance level of obnoxious odour and vapour



#### Flame Retardant Outer Media (V2425)

- Enhanced user safety to protect from welding spark



#### Superior Technology Micro Fine Filter Media

- Protects against respirable particulate suspended particulate matter while improving breathing comfort
- Composed of multiple layers: pre-filter, fine filter and skin comfort layer
- Made from special engineered fabrics which are extremely easy to breathe but also provide higher protection up to 0.3micron



#### Aluminum nose clip

- Leak-proof fit
- It does not permit eyewear fogging



#### Stay Cool Butterfly Vent Valve

- Provides breathing comfort and promotes easy communication
- Removes exhaled air, minimizes the risk of fogging eyewear
- Patented butterfly design which reduces heat build up inside the mask by 10°F
- Helps in breathing comfort and enhances respirator wear for a longer period



#### Transparent Valve Vent

- Transparent valve clearly demonstrates the performance of valve, it also supports fit verification



#### Unique Fit Adjuster Beads

- Unique fit adjusters present on the headband can be used to fit the user's face profile
- Convenient to retrieve while using
- Easy to don & suits personal adjustment requirements to provide a comfortable fit



#### Elastic Sewn Outside Filter Area

- Sewn head straps which provides better pull strength

### APPLICATION EXAMPLES

**Chemical  
Automobile**

**Battery  
Pharmaceuticals  
Ceramics**

Material handling, Material processing  
Painting, Powder coating, Welding,  
Maintenance work  
Lead handling  
Bulk drugs, Material handling  
Material mixing

**Metal Fabrication  
Agriculture  
Engineering**

**Effluent Treatment  
Plant**

Soldering, Welding, Metal pouring, Smelting  
Pesticides, Insecticide spraying  
Welding, Sand blasting, Buffing, Powder coating  
Painting, Cutting  
Maintenance

# V-2428

## Convex - Cup Seam Style

IS 9473



CML-0007143057

**ISI Approved**

### Superior technology micro-fine filter media

- Protects micro-fine respirable particulate matter
- Higher dust holding capacity
- Doesn't let the filter clog thereby increasing the respirator's life

### Color coded fittings

- Allows easy identification
- Denotes the level of protection

### Low profile design

Fits wide range of face contours

### Tough shell

Well-integrated structure maintains the shape disallowing collapse



### Stay cool butterfly vent valve

- Provides breathing comfort and promotes easy communication
- Effectively removes heat build-up



### Aluminum nose clip

- Leak-proof fit
- Disallows fogging of eyewear

### Unique fit adjusters

Provides optimum protection &amp; comfort

### Latex free textile elastic

- Long life
- Skin friendly
- Does not deform in high temperature

### Compatibility

Compatible with Venus head protection and eye protection devices

### Elastic sewn outside filter area


- Leakproof
- Avoids puncture

### Bi-lingual user instructions

For easy acceptance by different wearers



### VENUS V-2424 SLOV-V

 CLASS: FFP2 SLOV 

 Protection: Solid Dust / Oil Mist  
 Nuisance Level of Paint  
 mist & odour <TLV

M.U.L: Upto 12 x TLV

Transparent Exhalation Vent Valve

Item #	Colour	Elastic
12215	GREY	SEWN

### VENUS V-2426 SL-AC


 CLASS: FFP2 SL 

 Protection: Solid Dust / Oil Mist  
 Nuisance Level of Acid  
 gas <TLV

M.U.L: Upto 12 x TLV

Item #	Colour	Elastic
12076	BLUE	SEWN

### VENUS V-2427 SL-HF

 CLASS: FFP2 SL 

 Protection: Solid Dust / Oil Mist  
 Nuisance Level of HF-AC  
 odour <TLV

M.U.L: Upto 12 x TLV

Item #	Colour	Elastic
12199	LIGHT BLUE	SEWN

### VENUS V-2428 SL-AM


 CLASS: FFP2 SL 

 Protection: Solid Dust / Oil Mist  
 Nuisance Level of  
 Ammonia <TLV

M.U.L: Upto 12 x TLV

Item #	Colour	Elastic
12216	DARK GREEN	SEWN

### VENUS V-2425 SLOV-V

 CLASS: FFP2 SLOV 

 Protection: Solid Dust / Oil Mist  
 Nuisance Level of odour  
 Flame retardant outer layer

M.U.L: Upto 12 x TLV

Transparent Exhalation Vent Valve

Item #	Colour	Elastic
12185	GREY	SEWN

### Application examples

