
SINGLE HEADED HYDRANT VALVE



New Õʻʻj í Old Õj ™ẬStringers StreetẬ Chennai È™¹¹¹¹ i ẬTamilnaduẬIndiaÃ









FEATURES

- Single Headed Landing Valve manufactured in accordance with IS 5290 Type A
- Available in both the material Gun Metal and Stainless Steel
- Approval from Bureau of Indian Standards ISI Marked
 Inlet 75 mm with 63 mm size one nos, female outlet
- instantaneous coupling
- · Body is Red Painted and the Hand wheel is Black Painted
- Female Instantaneous Outlet is supplied in Polished Finish and free from burs and porosity

SPECIFICATIONS

Type: Single Headed Oblique Type Landing Valve

Body: Gun Metal IS:318 LTB -2

Stainless Steel IS:3444 Grade 1 and Grade 4

Hand Wheel: Cast Iron IS: 210

Inlet: 75 / 80mm NB Flanged Inlet

Outlet: 63mm Instantaneous coupling with Pull out type

lugs / Quick Release Lugs

Material: Gun Metal & Stainless Steel Size: 63mm / 2.5 inch

Size: 6
Performance

-

Test: Hydrostatic Test (Body Test): Tested at 21 Kgf/cm²

Water Tightness (Seat Test): Tested at 14 Kgf/cm² Flow Test: Min. 900 LPM discharge at 7 Kgf/cm²

Flange Drilling: 75 NB 3° (OD -200mm, PCD – 160mm, 4 Holes

19mm) or ANSI B 16.5 150#