TECHNICAL DATASHEET OF HOSE PIPE



CRC Super Synthetic fire Hose is made out of High Tenacity Synthetic Yarn to ensure fool proof performance The lining is seamless type of EPDM rubber compound for excellent protection against ageing and tackiness. The Synthetic jacket of the hose is completely inert againt attack from middle and fungus. Moreover, being a 100% synthetic it can be dried very easily o form small and compact rolls which can stored and moved around easily.

Performance & Salient Feature:

- 100% Polyester
- Rot Proof
- Withstands high pressure
- Resistance to abrasion, ageing, ozone, heat, sea water
- High Kink resistance
- Outstanding adhesion
- Flexible, Compact, Robust, Flat Folding, Easy Cleaning.

Approval

ISI marked under IS 636 : 2018 Type 1

Manufactured under ISO 9001:2015 quality systems

Application:

• Fire brigades • Refineries • Industrial Plants • Power Plants • Sailing Vessels • Other Prevail Industries

STANDARD LENGTHS 7.5 mtrs, 15 mtrs, 18.3 mtrs, 22.5mtrs & 30 mtrs		
Size	Proof Pressure (PSIG)	Burst Pressure (PSIG) (Min)
1 ½"(38mm)	325	550
2" (50mm)	325	550
2 ½"(63mm)	325	550
2 ¾"(70mm)	325	550





J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

