

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

XPR-5522GMX



THADHANI®
The Experts in Safety... Since 1947

NIGHTSTICK®
Life Depends on Light™



DUAL SWITCHES

Easily operate **independent flashlight and floodlight**, or simultaneous in Dual Light mode.

MAGNETS

Rare earth magnets in the tail and on the pocket clip **provide hands-free operation.**



The **soft, unfocused floodlight** is integrated into the housing, perfect for close-up illumination.



Dual body switches are perfectly placed for easy one-handed operation, even with gloves.



Integrated magnets in handle base and the pocket clip provide options for limitless hands-free usage.

FL1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	240 LUMENS	175 LUMENS	400 LUMENS
	8h	8h 30min	4h 45min
	178m		
	7964cd		
	2m		
	1m		

400 LUMENS



DUAL-LIGHT FLASHLIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5522GMX - 017398805643

CERTIFICATIONS

- CE, cETLus, ATEX, IECEX, MSHA, KOSHA, UKCA, INMETRO

CASE MATERIAL

- ABS polymer

LUMENS/RUNTIME

SPOTLIGHT

- HIGH: 240L, 8 hrs. runtime

FLOODLIGHT

- HIGH: 175L, 8.5 hrs. runtime

DUAL-LIGHT

- HIGH: 400L, 4.75 hrs. runtime

CANDELA

- HIGH: 7,964

BEAM DISTANCE

- HIGH: 178m

WATER RATING

- IP-67 (dustproof, waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.4 in (188mm)
- WIDTH: 1.7 in X 1.3 in (33mm x 43mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 9.9 oz (280g)

BATTERY

- Integrated Li-ion battery (included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Light with battery
- Lanyard
- Charger
- AC & DC cords

FL 1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	240 LUMENS	175 LUMENS	400 LUMENS
	8h	8h 30min	4h 45min
	178m		
	7964cd		

Bayco Products, Inc.
640 S. Sanden Blvd.
Wylie, TX 75098

Model XPR-5522GMX Safety Flashlight
Permissible Flashlight Assembly
APPROVAL No. 20-A160002-0
TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

MSHA

WARNINGS: 1) MSHA approved for use with one part number 5522-BATT rechargeable battery pack only.
2) The Model XPR-5522GMX Safety Flashlight is only to be charged on the surface, or underground in accordance with the applicable regulations pertaining to battery-charging stations (reference 30 CFR 75-340) with a Bayco Products, Inc. model 5522-CHGR1.
3) Do not open in areas where permissibility is required.

ATENÇÃO - UTILIZAR SOMENTE BATERIAS 5522-BATT.
ATENÇÃO - NÃO SUBSTITUIR A BATERIA QUANDO UMA ATMOSFERA EXPLOSIVA PUDE ESTAR PRESENTE.
ATENÇÃO - NÃO RECARREGUE A BATERIA EM ÁREAS CLASSIFICADAS.

CLASS I DIV 1 GRPS A-D T3
CLASS II ZONE 0 AEx ia IIC T3 Ga
CLASS II ZONE 20 GRP IIIC
Ex ia op ia IIC T3 Ga
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

Intertek ITS 16 ATEX201022X
ITS21UKEX0287X
IECEX ITS 16.0045X
-10°C ≤ Tamb ≤ +40°C IP54
3.7V/Cell
Input entity parameters for charging contacts on flashlight:
UL 4.75V
I: 500mA L: 0.0uH
P: 0.59W C: 0.0uF

CE 2575 UK CA 0359

CERTIFIED

CE Intertek Ex IECEX KCS UK CA 0359 INMETRO



THADHANI[®]
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com