

3AA

INTRINSICALLY SAFE INTRANT™ DUAL-LIGHT ANGLE LIGHT

XPP-5566RX/GX

**NIGHTSTICK®**  
Life Depends on Light™

HEAD ROTATES 90°

45°

EXCLUSIVE  
DOWNWARD FLOODLIGHT

DUAL  
LIGHT  
TECHNOLOGY



**Head rotates 90°** – directing beam exactly where it's needed most



**45° downward floodlight** lights an 8 foot walking area



**Easy-to-use with gloves**, the large switches **independently control** separate LEDs



Heavy-duty, clip and V-ring **securely holds tight to gear** in any situation

CERTIFIED



**205 LUMENS**

AVAILABLE IN HI-VIZ GREEN.

Web : [www.thadhanisafety.com](http://www.thadhanisafety.com), Mail : [info@thadhanisafety.com](mailto:info@thadhanisafety.com), PH : 044 - 4262 5223

**INTRANT®****DUAL-LIGHT™ ANGLE LIGHT****3AA****ITEM NUMBER/UPC**

XPP-5566RX (Red), 0 17398 80629 9  
XPP-5566GX (Green), 0 17398 80628 2

**MARKET APPLICATIONS**

Hazardous work environments, fire, rescue, industrial and automotive

**CERTIFICATIONS**

- CE, cULus, ATEX, IECEx, UKCA, InMetro, NFPA

**CASE MATERIAL**

- Glass filled nylon polymer

**LUMENS/RUNTIME****FLASHLIGHT**

- HIGH: 200L, 11 hrs. runtime
- MEDIUM: 110L, 18 hrs. runtime
- LOW: 60L, 33 hrs. runtime
- STROBE

**FLOODLIGHT**

- HIGH: 100L, 11 hrs. runtime
- MEDIUM: 40L, 18 hrs. runtime
- SURVIVAL: 20L, 33 hrs. runtime

**DUAL-LIGHT**

- 205L, 11 hrs. runtime

**CANDELA****FLASHLIGHT**

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

**BEAM DISTANCE****FLASHLIGHT**

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

**WATER RATING**

- IP-67 (dustproof and waterproof)

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 11.1 oz (315g)(with batteries)

**BATTERY**

- 3AA batteries (included)

**WARRANTY**

- Limited Lifetime Warranty

**WHAT'S INCLUDED**

- Angle light
- AA battery carrier
- 3AA batteries
- Instruction manual

| FL1 STANDARD | SPOT HIGH  | SPOT LOW  | DUAL-LIGHT |
|--------------|------------|-----------|------------|
|              | 200 LUMENS | 60 LUMENS | 205 LUMENS |
|              | 11h        | 33h       | 11h        |
|              | 401m       |           |            |
|              | 40256cd    |           |            |
|              |            |           |            |
|              |            |           |            |

Bayco Products, Inc. XPP-5566RX  
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
For use with Bayco Li-ion Battery Pack 5568-BATT1 or  
5568-CARRIER with 3 AA Energizer Type EN91 or E91  
batteries only

Atenção - NÃO SUBSTITUA A BATERIA QUANDO UMA ATMOSFERA  
EXPLOSIVA ESTIVER PRESENTE.  
Atenção - NÃO RECARREGUE A BATERIA EM ÁREA CLASSIFICADA.

CLASS I DIV 1 GRP A, D T4  
CLASS II & III DIV 2 GRP E, F, G T135°C  
CLASS I ZONE 0 AEx ia IIC T4 Ga  
Ex ia op is I Ma  
Ex ia op is IIC T4 Ga  
DEMKO 17 ATEX 1927  
UL220REX2426  
IECEx UL 17.0092  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell Alkaline  
3.7V/Cell Li-ion  
IP-67  
Um: 10V

Control Drawing: 5568-CERT-DWG1-03 For Battery Charger Connection see Instruction Manual Drawing: 5562-568-MECH-DWG1-09

SEE INSTRUCTION MANUAL  
VOIR MANUEL

MFG MM-YY

**CERTIFIED**

**THADHANI®**  
The Experts in Safety... Since 1947

**J.THADHANI & CO.**

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.

044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com