

2 AAA BATTERIES

INTRINSICALLY SAFE PENLIGHT

XPP-5410G

NIGHTSTICK[®]
Life Depends on Light[™]

**CLASS I
DIV 1**

**ATEX
ZONE 0
IECEx**


**IP-67
DUST/WATER
PROOF**




Limited lifetime warranty. Long lasting durability



Momentary or constant-on functionality. Only use it when you need it, or keep it on.



Streamlined integrated pocket clip. Rugged clip keeps your light handy and secure.



Impact and chemical resistant with a limited lifetime warranty.



30 LUMENS

INTRINSICALLY SAFE PENLIGHT

2 AAA BATTERIES

ITEM NUMBER/UPC

- XPP-5410G, UPC 0 1739880298 7

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive

CERTIFICATIONS

- CLASS I DIV 1: GRPS A-D T3
- CLASS II & III DIV 1: GRPS E-G T135°C
- CLASS I ZONE 0: AEx ia IIC T3 Ga
- CLASS I ZONE 0: Ex ia IIC T3 Ga
- ATEX CERTIFICATION: I M 1 Ex ia OP IS I Ma
- ATEX CERTIFICATION: II 1 G Ex ia OP IS IIC T3 Ga
- IECEX CERTIFICATION: Ex ia OP IS I Ma
- IECEX CERTIFICATION: Ex ia OP IS IIC T3 Ga

CASE MATERIAL

- Engineered polymer

FLASHLIGHT LUMENS/RUNTIME

- 30L, 18 hrs. runtime

CANDELA

- 107

BEAM DISTANCE

- 40m

DUST/WATER RATING

-ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.8 in (147 mm)
- HANDLE DIAMETER: 0.7 in (18 mm)
- HEAD DIAMETER: 0.9 in (23 mm)
- WEIGHT: 1.9 oz (54 g)

BATTERY

- AAA


WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Light
- 2 AAA batteries

FL 1 STANDARD



Permissible XPP-5410 Flashlight Assembly



APPROVAL No. 20-A140006-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: The Model XPP-5410 is MSHA approved for use with Energizer (Type E92), two Energizer (Type EN92), and Duracell (Type MX2400), Duracell (PC2400), and Duracell (EN92) batteries only. Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. The Model XPP-5410 must not be opened in area where permissibility required.



Intertek
ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3
CLASS II & III DIV 1 GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
Ⓜ I M 1 Ex ia op is I Ma
Ⓜ II 1 G Ex ia op is IIC T3 Ga

Ex ia op is I Ma
Ex ia op is IIC T3 Ga
Intertek ITS 13 ATEX27839X
ITS21UKEX0263X
IECEX ITS 14.0036X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline



Conforms to:

ANSI/UL STD 913, ANSI/UL
60079-0, ANSI/UL 60079-11
ANSI/ISA 60079-26

Certified to:

CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

CERTIFIED



THADHANI[®]
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com