

2 AA BATTERIES

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

XPP-5414GX

NIGHTSTICK®
Life Depends on Light™

**CLASS I
DIV 1**

**ATEX
ZONE 0
IECEx**

**IP-67
DUST/WATER
PROOF**

**HANDS-FREE
INTEGRATED
MAGNET**




Dual top-mounted switches.
Easy to use with gloves on.



Powerful rare-earth tail magnets
for additional hands-free use



Unfocused floodlight for close-up
illumination



Dustproof/Waterproof (IP-67)
and chemical/heat resistant for
any environment

**DUAL
LIGHT
TECHNOLOGY**



120 LUMENS



AVAILABLE AS A KIT

DUAL-LIGHT FLASHLIGHT

2 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5414GX (light only) 0 17398 80664 0
- XPP-5414GX-K01 (light with mount) 0 17398 80665 7
- NS-HMC7 (mount only) 0 17398 80666 4

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- CLASS I DIV 1: GRPS A-D T3
- CLASS II & III DIV 1: GRPS E-G T135°C
- CLASS I ZONE 0: Ex ia IIC T3 Ga
- ATEX Certification: II 1 G Ex ia op is IIC T3 Ga
- IECEx Certification: Ex ia op is IIC T3 Ga

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- 120L, 24 hrs. runtime

FLOODLIGHT

- 120L, 24 hrs. runtime

DUAL-LIGHT

- 120L, 24 hrs. runtime

CANDELA

- 3,100

BEAM DISTANCE

- 111 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
- HANDLE DIAMETER: 0.86 in (22 mm)
- HEAD DIAMETER: 1.28 in (33 mm)
- WEIGHT: 4.1 oz (116 g)

POWER SOURCE

- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

XPP-5414GX

- Flashlight
- Removable/Reversible Clip
- Instruction manual

XPP-5414GX-K01

- Flashlight
- NS-HMC7 multi-angle mount
- Removable/Reversible Clip
- Instruction manual

FL 1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	120 LUMENS	120 LUMENS	120 LUMENS
	24h	24h	24h
	111m		
	3100cd		
			
			



INTRINSICALLY SAFE
SECURITE INTRINSEQUE



SEE INSTRUCTION MANUAL
VOIR MANUEL
MFG MM-YY

Bayco Products, Inc. XPP-5414GX
640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

CLASS I DIV 1 GRPS A-D T3

CLASS II & III DIV 1 GRPS E-G T135°C

CLASS I ZONE 0 AEx ia IIC T3 Ga

Ex ia IIC T3 Ga

© II 1 G Ex ia op is IIC T3 Ga

Ex ia op is IIC T3 Ga

Intertek ITS 18 ATEX202366X

ITS21UKEX0268X

IECEx ITS 18.0005X

-20°C ≤ Tamb ≤ +40°C

1.5V/Cell with two

Energizer E91 or EN91

Meets the requirements of NFPA 1971-8.6 (2013)

CERTIFIED



IECEx



NFPA

UK CA 0359



THADHANI[®]
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com