

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT



THADHANI®
The Experts in Safety... Since 1947

NIGHTSTICK®
Life Depends on Light™



HEAD ROTATES 90°

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT

NIGHTSTICK
INTRANT

GRAB-N-GO
CHARGING BASE




Head rotates 90° – directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches **independently control** separate LEDs



Heavy-duty, clip and V-ring securely holds tight to gear in any situation



205 LUMENS

ALSO AVAILABLE IN SAFETY RED.

Web : www.thadhanisafety.com, Mail : info@thadhanisafety.com, PH : 044 - 4262 5223

DUAL-LIGHT ANGLE LIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2
XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8
XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA, KOSHA
- Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY

- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

FL1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		

Bayco Product, Inc. XPR-5568
640 S. Sanden Blvd., Wylie, TX 75098

UL LISTED
E-607755
ID: 4003544

Ex ia FLASLIGHT FOR USE IN HAZARDOUS LOCATIONS LANTERNA EXIA PARA USO EM LOCOS PERIGOSOS
For use with Bayco Li-ion Battery Pack 5558-SATT or 5558-CARBATT with 3 AAA Energizer Type D301 or E31 batteries only.
Para uso con la batería de iones de litio Bayco 5558-SATT o 5558-CARBATT con 3 baterías AA Energizer Tipo D301 o E31.

CLASS I DIV 1 GRP A D T1 CLASS II & III DIV1 GRP'S E-G T135°C CLASS I ZONE 0 AEx ia IIC T1 Ga CLASS I ZONE 0 AEx ia IIC T1 Ga

Ex ia up to 1Ma Ex ia up to 1Ma Ex ia up to 1Ma
Ex ia up to 1Ma Ex ia up to 1Ma Ex ia up to 1Ma

ELECTRICAL SAFETY INTRINSICALLY SAFE SECURITE INTRINSEQUE

US Patents 9,713,217 & 10,119,663

CE UK CA 2575 0359
Meets the requirements of NFPA-1971-3.6 (2013)

22-AV450-0250X

DEMKO 17-ATE-X 1527
UL2204EX2428
IECEx 11L 17 0080
20°C ≤ Temp ≤ +40°C
1.5V/Cell Alkaline
3 V/Cell Li-ion
IP-67
VDR: 10V

Control Drawing: 5558-CERT-DWG1-03
For Battery Charger Connection see Instruction Manual Drawing: 5552-08-MEC11-DWG1-09

SEE INSTRUCTION MANUAL VOIR MANUEL

MFG MM-YY

CERTIFIED									

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.

044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com



THADHANI®
The Experts in Safety... Since 1947