

LI-ION RECHARGEABLE

XPR-5582RX

XPR-5582GX



THADHANI®
The Experts in Safety... Since 1947

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

NIGHTSTICK®
Life Depends on Light™

1750

**POWERFUL
LUMENS**

INCLUDING HIGH & LOW



Rear green safety lights
provide visibility in smoke filled
applications



**Carry strap with seat belt style
buckle** for additional hands-free
use



**Convenient locking snap-in
charger** included



Dustproof/Waterproof (IP-67) and
chemical/heat resistant for any
environment

180° DOWNWARD ROTATION



AVAILABLE IN MULTIPLE COLORS



FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
	2m 1m	

1750 LUMENS

INTEGRITAS™

LANTERN

LI-ION RECHARGEABLE**ITEM NUMBER/UPC**

XPR-5582RX (Red), UPC# 0 17398 806824
 XPR-5582GX (Green), UPC# 0 17398 807029

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position
- US Patent 9,713,217

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 1750L, 5 hrs. runtime
- LOW: 600L, 11 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 81,250
- LOW: 27,083

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 552m
- LOW: 325m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm
- WIDTH: 4.26 in / 10.8 cm
- DEPTH: 5.83 in / 14.8 cm
- WEIGHT: 2 lbs. 11 oz. / 1219 g

BATTERY

- Rechargeable Li-ion battery pack

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Lantern
- Li-ion rechargeable battery pack
- Locking snap-in charger (5582-CHGR1)
- AC power supply
- DC direct wire kit with in-line fuse
- Removable shoulder strap
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
	2m	
	1m	



Bayco Products, Inc. XPR-5582
 640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 2 GRP'S A-D T3
 CLASS II & III DIV 2 GRP'S F-G T135°C
 CLASS I ZONE 2 Group IIC T3
 -20°C ≤ Tamb ≤ +40°C
 3.7V/cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.
 AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.
 WARNING: Risk of ignition - Do not charge batteries in a hazardous area.
 AVERTISSEMENT: Danger d'inflammation - Ne pas charger les piles dans une zone dangereuse.

CERTIFIED**NFPA**

AVAILABLE IN MULTIPLE COLORS



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
 Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com