



**THADHANI**<sup>®</sup>  
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.

044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com

**SURVIVOR**<sup>®</sup>

**RIGHT-ANGLE, SAFETY RATED  
FIREFIGHTER'S FLASHLIGHT**

**The Survivor features a low-profile bezel that doesn't interfere with gear and equipment. A reinforced D-ring provides forward-hanging orientation. Safety-rated for Class I, Div. 1 environments.**



Low-profile design doesn't interfere with gear and equipment



Interchangeable Smoke-Cutter<sup>®</sup> plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

Rubber dome push-button switch easy to use with gloves

Rugged nylon polymer body is virtually indestructible

No tools needed to change batteries



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation

Specialized optic combines low profile with strong performance and a wide beam

**DUAL POWER SOURCE:**  
Rechargeable NiMH battery also accepts (4) "AA" alkaline batteries



High, low, emergency flash and moonlight modes:

- High for a super-bright, smoke piercing beam: 175 lumens; 405m beam distance; runs 3.5 hours (NiMH); runs 4 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 13 hours (NiMH); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours
- Moonlight mode provides low-level lighting for battery conservation: runs 20 days

Optimized electronics provide regulated intensity

Unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel

IPX4-rated; water-resistant; 2m impact resistance tested

7.06 in. (17.92 cm); NiMH: 18 oz. (510g); Alkaline: 13.7 oz. (388g)

Class I & II, Division 1, Groups C, D, E, F, G, Class III, T-Code: T4; Class I, Division 2, Groups A, B, C, D, T-Code: T4

Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

Limited Lifetime Warranty

Visit streamlight.com for full warranty information

ORANGE	YELLOW	BLACK	DESCRIPTION
90505	90515	90525	Survivor - 230V AC/12V DC
90506	90516	90526	Survivor - 240V AC/12V DC
90503	90513	90523	Survivor - 120V AC/12V DC
90500	90510	90520	Survivor - without charger
90540	90541	90545	Survivor - alkaline

Increased output with added features, the C1D1 safety rated Survivor X right-angle light is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



**New charger design:**

- Survivor X securely locks into the charger - fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



Rubber dome push-button switch easy to use with gloves  
Features battery life indicator



Battery life indicator in switch:  
— Green indicates full charge  
— Turns red when battery is nearing low voltage  
— Flashes red continuously when 15 minutes left of battery life

Unbreakable polycarbonate lens with silicone anti-scratch coating  
Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible

No tools needed to change batteries



**High, low and emergency flash modes:**

- High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-Ion); runs 5 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-Ion); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours

Optimized electronics provide regulated intensity

IP67-rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested

Uses rechargeable lithium ion battery (charges in 5 hours) or three alkaline batteries

7.06 in. (17.92 cm); Li-Ion: 12.2 oz (346g); Alkaline: 12.8 oz (363g)

Class I & II, Division 1, Groups A, B, C, D,E, F, G; Class III, T-Code: T3/T4

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position

Limited Lifetime Warranty

Visit streamlight.com for full warranty information

ORANGE	YELLOW	DESCRIPTION
90953	90963	Survivor X - 230V AC/12V DC
90952	90962	Survivor X - 120V/100V AC/12V DC
90950	90960	Survivor X - Alkaline