



Scan Here For More Info



INDUSTRY	IDEAL APPLICATIONS	
Chemical	Chemical handling	
Pharmaceutical	Labs	
Oil & gas	Paint shop	
Iron & steel	Grinding	
Automotive	Medical application	

UD 49- Safety Goggles



STANDARD: 🔄 IS 5983, ANSI Z87.1, EN 166, CE

SPECIAL FEATURES













COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Single & cylinder lens
Frame	PVC	Flexible fitting goggle with 4 point ventilation system
Nose piece	PVC	Universal integral to frame
Head band	PP elastic	Adjustable for all head size

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Polycarbonate	1	2-1.2	B (120m/s)	К	75 g.

FEATURES

Polycarbonate lens with soft PVC frame

Fully adjustable headband attached to fits most users

Soft frame conforms to facial contours for restful & long time use

Hard coating on lens

Lens filters out 99.9% of harmful UV light

Lens provides medium velocity impact & splash protection around the eyes

Universal fit soft nose bridge conforms to facial contours to ensure a comfortable fit

4 point venting system that circulates air, yet prevent dust

Over the glass protective eyewear for all day wear

Suitable for different work environment & for both men and women

APPLICATION

Protects eyes exposed to medium level impacts

Best used for protection agains flying small fragments, liquid splashes, fumes, sparks etc.

Also protects against irritating mist and potentially infectious materials ($\mbox{Lab}\mbox{ environment}$)

STORAGE

Can be stored in the dark for up to 2years

Do not store in direct / high heat or sunlight as this may distort the colour $% \left(1\right) =\left(1\right) \left(1\right) \left($

Can be stored and transported in their original cartons at ambient temperature (0° C to $+30^{\circ}$ C)

CLEANING	PACKING
Clean it with the soft cloth	200 pieces per carton



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

