#### HOLD-IT

Description: Fabric supported fully coated natural rubber gauntlet with suede palm

Features & Benefits:

- \* Two piece liner without seams in the working area eliminates hand irritation
- \* Anatomically shaped to provide good fit
- \* Bacteriostatic and fungistatic additives
- \* Compliant with (EC) No. 1935/2004 & EU 10/2011 (Blue)
- \* Cotton interlock liner absorbs perspiration and adds to comfort
- \* Durable and washable
- \* Extended gauntlet cuff to protect forearm
- \* Fully coated for extra protection
- \* Ingredients comply with FDA regulations for food contact (Blue only)
- \* Liquid proof for use in wet conditions
- \* Safe for food handling
- \* Sude finished palm for safe handling and good grip

Applications: Construction, Logistics and warehousing, Facility maintenance, Household use

Elastomer: Natural rubber
Thickness: 1.40 +/- 0.10 mm
Lining: Interlock


Former: Plain CIII
Exterior: Suede finished palm

Cuff Types: Gauntlet

Treatments:

CE Certification:

Colours: Blue B9 on Blue B8



 $against\ standards\ EN\ 374-1:2016+A1:2018,\ EN\ 388:2016+A1:2018\ ,EN\ 374-5:2016,\ EN\ ISO\ 21420:2020\ and\ A1:2018,\ EN\ A$ 

EN 407 : 2020

Conforms to: ASTM D4679 of 2002

Physical	Size	Palm	Wrist	Cuff	Length
Dimensions:	6	208	216	274	300
	7.5 (M)	222	228	288	300
	8.5 (L)	234	240	296	300
	9 (L+)	242	254	304	300
	10 (XL+)	252	268	308	300
	11(XXL+)	264	272	310	300

Circumference in mm, +/- 5 mm Tol. +/- 10 mm

EN 374-4

Revision:7

Protection against Chemical hazards		Performance	Degradation %
EN ISO 374-1/TYPE A			
	* Methanol (A)	Level 6	12.7
( ,#]	* Sodium hydroxide 40% (K)	Level 6	-83.4
	* Sulphuric acid 96% (L)	Level 4	-62.9
	* Nitric acid 65% (M)	Level 6	-66.4
AKLMNPST	* Acetic acid 99% (N)	Level 3	-58.7
	* Hydrogen peroxide 30% (P)	Level 6	-82.3

Note: Printed copies are valid only on the date printed

Printed Date: 07-Feb-2023 Published Date: 14-Nov-2022



#### J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



## **HOLD-IT**

* Formaldehyde 37% (T)	Level 6	-29.4
* Hydrofluoric acid 40% (S)	Level 5	X

# Protection against Mechanical hazards

EN 388



- \* Abrasion resistance
  \* Blade cut resistance
  \* Tear resistance
- \* Puncture resistance Level 1
  \* TDM cut resistance X

## Protection against Micro-organisms risk

EN 374-5



- \* Protection against bacteria and fungi
- \* Protection against viruses

Pass

n/a

Performance

Performance

Performance

Level 4

Level 1

Level 3

EN 407



* Limited Flame Spread	X
* Convective heat	X
* Contact heat	Level 1
* Radiant heat	X
* Small splashes of molten metal	X
* Large quantities of molten metal	X