



H33NBG

#### Features:

The optimal combination of cut resistance, comfort and dexterity, Open back configuration for better ventilation,

Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue, Colour coded over lock binding helps to identify different sizes,

Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

## H33NBG

#### Material used

Coating: Palm and finger tips- NBR compound coated

Liner blended UHMWPE, Glass, Polyamide, Polyester, Spandex fibre

Binding –Colour coded over lock binding polypropylene yarn (07-Red, 08-Yellow, 09-Brown, 10-Black)

#### Sizes

7, 8, 9, 10, 11

#### Color

Liner Color: Grey

Coating Color: Black

#### Specifications

Gauge: 13

Weight: 720-860 g/dzp

Finishing: Sandy Finish



**THADHANI®**  
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223



info@thadhanisafety.com



www.thadhanisafety.com



## NITRILE GLOVES

*Cut Resistant Level 5 Seamless  
Nitrile Coated Gloves Blended  
with Steel based Fiber, Sandy  
Finish.*



## Safe hands!!

### Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

### Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

*Our engineered high cut resistant UHWMPE & GLASS blended Tuf-Tec® yarn with nitrile coated surface provide, dexterity and mechanical resistant*

### Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

### Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

### Packaging Instruction:

1 dozen pairs in a polybag  
10 poly bags in a carton  
120 pairs in a carton



Performance according to EN 388:2003

- 4. Resistance to abrasion (from 0 to 4)
- 5. Resistance to cut (from 0 to 5)
- 4. Resistance to tear (from 0 to 4)
- 3. Resistance to puncture (from 0 to 4)



### Applications:

#### Automotive Aftermarket:

Chassis assembly, body trimming  
Foundry operations

#### Machinery and Equipment:

Handling materials with sharp or rough edges  
Handling metal sheets & panels  
Handling parts in high heat areas  
Handling parts with sharp, rough edges



**THADHANI**  
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com