

Features:

Seamless knitting construction ,Open back configuration for better ventilation,

Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue.

Colour coded overlock binding helps to indentify different sizes,

Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

M35NBV

Material used

Palm: Nitrile coated palm over nylon spandex blended liner

Coating – Coated with NBR &PU based compound. Foamy Finish

Liner - Nylon & Spandex blended

Gauge - 15

Cuff - Knitted

Binding – Fused binding, colour according to sizes: 07 – Red, 08 – Yellow, 09 - Brown, 10 - Black

Sizes

7, 8, 9, and 10

Color

Back: grey Palm: black

Specifications

Gauge: 15

Weight: 540(±10g) Finishing: Foamy Finish



NITRILE GLOVES

15 gauge, black coloured Nylon-Spandex blended foamy finished Nitrile gloves provide durable hand protection and supreme abrasion resistance with an outstanding dexterity



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.





Safe hands!!

Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

Patented Foamyflex ® finishing provides superior comfort and durability and performance

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines

Instructions for cleaning:

No specific cleaning or maintenance for this type of glove.

Packaging Instruction:

1 dozen pairs in a polybag 10 poly bags in a carton 120 pairs in a carton (240 pairs/carton option also available)



Performance according to EN 388:2003:

- 4 Resistance to abrasion (from 0 to 4)
- 1 Resistance to cut (from 0 to 5)
- 3 Resistance to tear (from 0 to 4)
- 1 Resistance to puncture (from 0 to 4)





Applications:

Construction Works.
Lumber and mill works
Metal/aluminium sheet handling
Machine parts assembling disassembling
Gardening
Agricultural applications
Motor industry
Parts assembly
Painting job



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.

