

P35NBG

Features:

Seamless knitting construction Open back configuration for better ventilation.

Ergonomically correct design conforms snugly to the natural shape of the hand, increasing comfort and reducing hand fatigue.

Colour coded overlock binding helps to indentify different sizes (07- Red, 08-Yellow, 09- Brown, 10- Black).

Nitrile dipped palm provides excellent puncture and abrasion resistance properties, also provide assistance to handling chemicals and oils.

P35NBG

Material used

Palm: 1.1 mm thick sandy finished palm

Coating: - NBR compound coated

Liner:- Polyester

Binding: - Polypropylene yarn

Sizes

7, 8, 9, 10, 11

Color

Liner Color: Gre Coating Color: Black

Specia. ations

Gauge: 15

Weight: 500-700 g/dzp Finishing: Sandy Finish



NITRILE GLOVES

Grey Polyester 15 gauge seamless liner coated with black coloured Nitrile compound, Sandy finish.



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



044 - 4262 5223





Safe hands!!

Limits to use

Do not use this glove out of its usage specifications defined in the instructions above. This glove does not contain substance known as being carcinogenic, neither toxic, nor likely to cause allergies to the sensitive people.

Instructions for storage:

Store in a cool, dry place; away from frost and light in their original packaging.

Polyester seamless with Nitrile coating ensures protection against chemical as well as mechanical threats

Warning

Gloves not so se w rn when there is a risk of entangle nent by mo ing parts of machines

Instruction. for cleaning:

No specific cleaning or maintenance for this type of glove.

Packaging Instruction:

1 dozen pairs in a polybag 10 poly bags in a carton 120 pairs in a carton (240 pairs/carton option also available)



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



- 4: Resistance to abrasion (from 0 to 4)
- 1: Resistance to cut (from 0 to 5)
- 2: Resistance to tear (from 0 to 4)
- 1: Resistance to puncture (from 0 to 4)
- X: TDM blade cut resistant level (from A to F)





Applications:

Construction Works. Lumber and mill works Metal/aluminium sheet handling Machine parts assembling disassembling Gardening Agricultural app; ications Motor industry











