

BL22

Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Construction	Work At Height
Metals & Mining	Ladder Climbing
	Fall Arrest
Cement	Rescue

SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

ROPE MATERIAL

10.5mm Kernmantle Rope

FEATURES

Energy Absorbing Double Braided Rope Lanyard

One side (Lanyard End) connected with SH-60 scaffolding hook and on other side connected with EASY 308 Carabiner

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

10 pieces per carton



STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

BREAKING STRENGTH

22kN (Min)

LANYARD LENGTH

1.8 mm (Hook to Hook)

MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com