

## EL22

### Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Metals & Mining	Work At Height
Pharmaceuticals	Ladder Climbing
Chemicals	Fall Arrest
	Rescue

#### SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

#### ROPE MATERIAL

35m (+/- 1mm) wide Elasticated Polyester Webbing

#### FEATURES

Energy Absorbing Double Elasticated Webbing Lanyard for fall arrest

One side carabiner and other side two tower hooks, made of Aluminum Alloy, conforming to EN362

Elasticated webbing extends as per user requirement, Relaxed Length 1.4m, Extended Length 1.8m

Light Weight & High Strength Lanyard

#### CLEANING

Use clean piece of cloth to wipe the dust

#### PACKING

10 pieces per carton



#### STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

#### BREAKING STRENGTH

23kN (Min)

#### LANYARD LENGTH

1.8 meter (Hook to Hook)

#### MARKINGS

Manufacturers Logo

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

#### STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.



**THADHANI**®  
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com