

**WL01**  
Safety Lanyard

STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002 

INDUSTRY	IDEAL APPLICATIONS
-	Work at Height
-	Fall Arrest

**SPECIAL FEATURES**



LIGHT WEIGHT



FALL RESTRAINT

**ROPE MATERIAL**

44m (+/- 1mm) wide webbing energy absorbing single Lanyard

**FEATURES**

Energy Absorbing Single Polyester Webbing Lanyard

Shock absorber with EASY 308 karabiner and other side EASY SH60 scaffolding hooks.

**CLEANING**

Use clean piece of cloth to wipe the dust

**PACKING**

10 pieces per carton



**STITCHING THREAD**

High Tenacity Virgin Multifilament Polyester

**BREAKING STRENGTH**

23kN (Min)

**LANYARD LENGTH**

2 Mtr (Hook to Hook)

**MARKINGS**

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

**STORAGE**

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.