

WL04
Safety Lanyard

STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002 

INDUSTRY	IDEAL APPLICATIONS
-	Work at Height
-	Fall Arrest



SPECIAL FEATURES



LIGHT WEIGHT



FALL RESTRAINT

ROPE MATERIAL

44m (+/- 1mm) wide webbing energy absorbing single Lanyard

STITCHING THREAD

High Tenacity Virgin Multifilament Polyester

FEATURES

Energy Absorbing Single Polyester Webbing Lanyard

With one side EASY 308 karabiner and other side EASY SH 18 hooks.

BREAKING STRENGTH

23kN (Min)

LANYARD LENGTH

2 Mtr (Hook to Hook)

MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

CLEANING

Use clean piece of cloth to wipe the dust

STORAGE

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

PACKING

10 pieces per carton

