

IKAR HAS

Controlled Descent Device

STANDARD: CONFORMING TO EN360:2002, EN 341:2011 

INDUSTRY	IDEAL APPLICATIONS
Process Plant	Confined Space Rescue
Manufacturing Unit	Tanker inspection
Utility Sector	Maintenance at Vessel

SPECIAL FEATURES



RESCUE



H-SHAPED



EASY TO USE



STRONG



WATER RESISTANT

ROPE MATERIAL	ROPE DIA	ROPE LENGTH
Steel rope	Ø 4.8 mm	18mtr., 30mtr.
HOUSING	BREAKING STRENGTH	NOMINAL LOAD
Aluminum	25 kN	136 kgs.



FEATURES

Initially work as a normal fall arrest device, but then automatically lowers the user at an approximate speed of 0.9 m/sec following activation of the centrifugal coupling.

STORAGE

Store the block in a dry & normal temperature.

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

1 piece per box

MARKINGS

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approval & EN standard



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com