

**UB 102 JKO**

Safety Jacket Harness

STANDARD : EN 361 CE Marked 

INDUSTRY	IDEAL APPLICATIONS
Aluminium Plant	
Steel Plant	
Pharmaceutical	
Cement	Overhead Loading Unloading & Tarpaulin Covering
Chemical	
Food & Beverages	

SPECIAL FEATURES	
	
	
CLASS-A	CLASS-L

WEBBING MATERIAL	JACKET COLOUR
Fray-proof dope-dyed polyester webbing	
Metal buckles of high strength alloy steel	Red & Black

JACKET TYPE
Executive type of reflective jacket harness with reflective strip



WEBBING BREAKING STRENGTH		METAL COMPONENTS	
22kN (Min)		Metal buckles of high strength alloy steel	
STITCH THREADS MATERIAL	STITCH THREADS COLOUR	HARNESS COLOUR	WEIGHT
High-strength polyester stitching	White	Yellow & Black	750 grams (Approx.)

TEST COMPLIANCE - STATIC STRENGTH	TEST COMPLIANCE - DYNAMIC STRENGTH
Tested at each attachment element with a force of 15 KN applied for 3 min.	When tested at each Fall Arrest Attachment element with a torso dummy of 100 Kg mass, the full body harness withstands drop tests with a free fall distance of 4 meters

### FEATURES

- One dorsal D-ring for fall arrest
- Two textile chest attachment loop fall arrest
- Integrated reflective Jacket Harness with reflective strip
- Easy and fast to put on zipper system
- Ideally positioned sit-strap for extended comfort
- Built-in dual colour webbing for easy orientation
- Size adjustment straps at chest, shoulder and thighs

### MARKINGS

- Manufacturers Logo, details & mailing address
- Model No., Batch No., Serial No.
- Year of Manufacture
- Material
- Approvals CE & IS marking
- Instruction Pictogram

### STORAGE

- Store the harness in a dry area away from ultraviolet rays.
- Do not store in direct/ high heat or sunlight as this may distort the Colour.
- Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

### CLEANING

- Use Clean piece of cloth to wipe the dust

### PACKING

- 1 piece per bag