



Scan Here For More Info



## UD 50 - Safety Spectacle

STANDARD : ANSI Z87.1, EN 166, CE

INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

### SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Wrap around with angle side protection
Frame	Polycarbonate	Brow bar type
Nose piece	Polycarbonate	Integral to lens
Sleeve	Nylon	5 length position adjust
Temple	Nylon	Spatula, extendable
Hinga	Nylon	3 barrel type
Screw	Stainless Steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	30 g.

### FEATURES

- Brow guard temple with polycarbonate lens
- Lens provides side protection
- Hard coating on lens
- Single piece lens, filters out 99.9% of harmful UV light
- Lens provides perfect impact protection around the eyes
- Length adjustable temple for all head sizes
- Modern temple design & soft nylon temple tips contours to fit head shapes without stress
- Credibly light, resilient & durable protective eyewear for all day wear
- Fashionable design resembles spectacle, suitable for both men and women
- Suitable for different work environment

### APPLICATION

- Protects eyes exposed to low-level impacts
- Best used for protection against flying small fragments

### STORAGE

- Can be stored in the dark for up to 2years
- Do not store in direct / high heat or sunlight as this may distort the colour
- Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

### CLEANING

- Clean it with the soft cloth

### PACKING

- 100 pieces per cartoon