



Scan Here For More Info



ing
ations

UD 71 - Safety Spectacle

STANDARD: IS 5983, ANSI Z87.1, EN 166, CE

SPECIAL FEATURES









COMPONENT	MATERIAL	ADVANTAGE		
Lens	Polycarbonate	9.75 base curve, wrap around design w/side protection		
Nose piece	Polycarbonate	Universal, integral to lens		
Temple	Polycarbonate	Spatula		
Hinge	Polycarbonate	5 barrel type		
Screw	Stainless steel	Standard hinge screw		

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	К	20 g.

FEATURES

Polycarbonate temple with polycarbonate lens

Snug-fitting wrap around lens provides perfect impact protection around the eyes

Hard coating on lens

Lens filters out 99% of harmful UV light

Close-fitting unitary front with dual 9.75 base curvature offers wide and unobstructed vision

Soft temple tips

Incredibly light, resilient & durable protective eyewear for all day wear

Fashionable design resembles spectacle, suitable for both men and women

Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts

Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour $% \left(1\right) =\left(1\right) \left(1\right) \left($

Can be stored and transported in their original cartons at ambient temperature (0 $^{\circ}$ C to +30 $^{\circ}$ C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton



J.THADHANI & CO.

New #12/ Old #28, Stringers Street, Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com www.thadhanisafety.com