



Scan Here For More Info



UD 81 - Safety Spectacle

STANDARD : IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY

Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS

Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	10 base curve, wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula with soft tip end
Tip	PVC	Slip on the temple
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	20 g.

FEATURES

Polycarbonate temple with polycarbonate lens
Snug-fitting wrap around lens provides perfect impact protection around the eyes
Hard coating on lens
Lens filters out 99.9% of harmful UV light
On-piece lens, with dual 10 base curvature
Lens offers users the clearest and the most panoramic view without obstruction
Modern temple design & soft temple tips contours to fit head shapes without stress
Incredibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

100 pieces per carton



THADHANI®
The Experts in Safety... Since 1947

J.THADHANI & CO.

New #12/ Old #28, Stringers Street,
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223
info@thadhanisafety.com
www.thadhanisafety.com