

**WL20**  
Safety Lanyard

STANDARD : CERTIFIED TO EN 354:2010, EN 355:2002 

INDUSTRY	IDEAL APPLICATIONS
-	Work at Height
-	Fall Arrest

**SPECIAL FEATURES**



LIGHT WEIGHT



FALL RESTRAINT

**ROPE MATERIAL**

44m (+/- 1mm) wide Polyester Webbing

**FEATURES**

Energy Absorbing Single Polyester Webbing Lanyard

One side (Lanyard End) connected with SH-60 scaffolding hook and on other side connected with

**CLEANING**

Use clean piece of cloth to wipe the dust

**PACKING**

10 pieces per carton



**STITCHING THREAD**

High Tenacity Virgin Multifilament Polyester

**BREAKING STRENGTH**

23kN (Min)

**LANYARD LENGTH**

1.8 mm (Hook to Hook)

**MARKINGS**

Manufacturers Logo, details & mailing address

Model No., Batch No., Serial No.

Year of Manufacture

Material

Approvals & CE

Instruction Pictogram

**STORAGE**

Store the harness in a dry area away from ultraviolet rays.

Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.



**THADHANI**®  
The Experts in Safety... Since 1947

**J.THADHANI & CO.**

New #12/ Old #28, Stringers Street,  
Chennai - 600001, Tamilnadu, India.



044 - 4262 5223

info@thadhanisafety.com

www.thadhanisafety.com